

HORIZONTAL CLAMPING SYSTEM

Moving clamps / locators for cl	amping body	
Clamp made of spring steel (works with the body pressure screw)		
Low moving clamp / locator clamping height 2.5 mm	09-615	
Standard moving clamp / locator clamping height 4.7 mm	09-610	
Raised moving clamp / locator	09-620	

Extra-raised moving clamp / locator clamping height 13.5 mm

clamping height 8 mm




Table-mounted clamps / locators (stops) Clamp made of spring steel

(with clamping screw and \emptyset 18 mm locator)

(with clamping set on and b to min recutor)	
Low clamp / locator clamping height 2.5 mm	
Mounted with M 10	09-143
Mounted with M 12	09-144
Standard clamp / locator clamping height 6 mm	
Mounted with M 10	09-140
Mounted with M 12	09-141
Extra-raised clamp / locator clamping height 13.5 mm	
Mounted with M 10	09-142

Standard double ended clampclamping height 6 mmfor clamping two facing workpieces09-145Mounted with M 1009-145Mounted with M 1209-147

Table-mounted clamps / locators 09-140 / 141 / 142 / 143 / 144

Table-mounted clamps / locators

clamping element. See following page !

lengthways

When the clamps are used


slots, the use of anti-sliding

T-nuts is recommended in order to resist the force


of pressure exerted by the

along

the



09-145 / 147



Moving clamps / locators 09-610 / 615 / 620 / 625




Table driving clamp 09-065 / 068

